

Y-bearing flanged units, Y-TECH housing, square flange, grub screw locking, food compatible grease

Product information

Dimensions					Basic load ratings		Limiting speed with shaft tolerance h6	Mass	Designations Bearing unit	Housing	Bearing
d	A ₁	J	L	T	C	C ₀					
mm					kN		r/min	kg	-		
20	30	63,5	86	37,3	10,8	6,55	5000	0,26	FYKC 20 NTH	FYKC 504 N	YAR 204-2RF/HV
20	30	63,5	86	37,3	12,7	6,55	5000	0,26	FYKC 20 NTR/VE495	FYKC 504 N	YAR 204-2RF/VE495
25	31	70	95	38,8	11,9	7,8	4300	0,33	FYKC 25 NTH	FYKC 505 N	YAR 205-2RF/HV
25	31	70	95	38,8	14	7,8	4300	0,33	FYKC 25 NTR/VE495	FYKC 505 N	YAR 205-2RF/VE495
30	33	82,5	108	42,2	16,3	11,2	3800	0,48	FYKC 30 NTH	FYKC 506 N	YAR 206-2RF/HV
30	33	82,5	108	42,2	19,5	11,2	3800	0,48	FYKC 30 NTR/VE495	FYKC 506 N	YAR 206-2RF/VE495
35	35	92	118	46,4	21,6	15,3	3200	0,66	FYKC 35 NTH	FYKC 507 N	YAR 207-2RF/HV
35	35	92	118	46,4	25,5	15,3	3200	0,66	FYKC 35 NTR/VE495	FYKC 507 N	YAR 207-2RF/VE495
40	39	101,5	130	54,2	24,7	19	2800	0,87	FYKC 40 NTH	FYKC 508 N	YAR 208-2RF/HV
40	39	101,5	130	54,2	30,7	19	2800	0,87	FYKC 40 NTR/VE495	FYKC 508 N	YAR 208-2RFG/VE495